

PTFE LAMINATED

CL3320 ULTRA BROWN/BLACK

CL3320 ULTRA BROWN/BLACK combines the features of multi-layer fluoropolymer cast film with the mechanical properties of fibreglass-reinforced fabric.

Common applications include: Grilling; Heat sealing; Lamination; Chemical barriers; Containment.

TYPICAL PROPERTIES

| PROPERTY | METRIC | | IMPERIAL | | TEST METHOD |
|------------------------|--------------|------------------|--------------|--------------------|----------------|
| Standard Widths | 1015, 1350 | mm | 39.9, 53.1 | in | - |
| Weight | 563 | g/m ² | 17.4 | oz/yd ² | FTMS 191A-5041 |
| Thickness | 0.260 | mm | 12 | mil | FTMS 191A-5030 |
| Tensile Strength | 480 x 380 | N/cm | 300 x 265 | lb/in | FTMS 191A-5102 |
| Trap Tear Strength | 60 x 40 | N | 23 x 22 | lb | FTMS 191A-5136 |
| Temperature Resistance | -150 to +250 | °C | -240 to +500 | °F | - |

FEATURES AND BENEFITS

- Thermally stable from -150 to +260 °C
- Chemically inert
- Non-stick and washable
- Dimensionally stable
- Non-flammable/fire resistant
- Low electrical losses
- Food compliant and hygienic
- Excellent barrier properties

CONTACT US

+353 65 90 80 170

contact@versivcomposites.com

Versiv Composites Limited
Kilrush, Co. Clare, V15 NW27, Ireland

www.versivcomposites.com

IMPORTANT: Pictures shown are for illustration purpose only. The values presented are typical values and should not be used for specification purposes. Contact your representative for more information. It is the user's responsibility to ensure the suitability and safety of Versiv Composites products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Versiv Composites Limited assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication, or application of the products into which the materials are incorporated by purchaser and/or user.

WARRANTY: We warranty specifications at delivery and honour claims for such breach of warranty for six (6) months after delivery. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential arising out of the use, misuse or inability to use this product(s). VERSIV COMPOSITES LIMITED DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Version 2 • Valid 10/2025 • Supersedes all previous versions

